



## Technical Data Sheet

### GT-5738 Architectural Coating

GT Products 5738 is a odorless reactive siloxane polymer emulsion designed for architectural coating applications to impart water repellency and stain resistance.

#### Typical Properties:

Diluent :	Water.
Solids Content:	12 -16 %
Color:	Off White
Specific Gravity:	0.99 (Approximately)
Emulsification Type:	Cationic
Viscosity:	Brookfield viscosity #1@100 = 20 cs
Ph Level:	8 -11

#### Application:

GT Products 5738 is a one component system designed to be used as received. When coating substrates with varying degrees of absorption, it is recommended that a light second coat be applied.

The information, data, and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyers' process. SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of an product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of GT Products, Inc. or GT Products subsidiaries.