



## Technical Data Sheet



### GT 6380 Water Repellent

GT Products™6380 is a low VOC, high-flashpoint water repellent.

#### Application

The product was designed to be used on architectural substrates to seal them and to promote water repellency and stain resistance.

#### Storage

Store in a hermetically sealed container in temperatures no higher than 40°C.

#### Safety Information

See the material safety data sheet associated with the product for more information.

#### Product Data

Properties	Characteristics
Appearance	Clear Liquid
Solid Content (%)	90
Flash Point, (°F)	155
Specific Gravity, (g/mL)	0.98
Viscosity, (cP)	94

The information, data, and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyers' process. SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of an product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of GT Products, Inc. or GT Products subsidiaries.