



## Technical Data Sheet

### GT-5466 One Part RTV Silicone

GT Products X-5466 is a one part sprayable adhesive. No additional catalyst or mixing are required. The low viscosity of this material permits application by either brush or spray.

#### Typical Properties

Color	Translucent
Specific Gravity	.89—.95
Viscosity	225 cp (Brookfield #7 @ 20 rpm)
Hardness Shore A	45
Temperature Range	1mm for 5 min. @ 150 <sup>0</sup> C
Shelf Life	3 Months
Storage	Closed container at Room Temperature.

#### Tensile Strength when applied to various materials.

Epiall 1908 B	741 psi
Ultem 2210 R	679 psi
Fortron	559 psi
PES	580 psi

The information, data, and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyers' process. SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of an product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of GT Products, Inc. or GT Products subsidiaries.