## GT Products Platinum Catalyst Systems, Adhesives & Additives for HCR Silicone

| Process     | Product    | Description                   | Use level pph | Advantage   |
|-------------|------------|-------------------------------|---------------|---|
| MOLDING     | GT 5239A   | Platinum Catalyst             | 1             | Achieve higher strength physicals w/GP base   |
|             | GT 6519B   | XL/inhibitor                  | 2.5           | Long mixed pot life ~ months  |
|             | GT 6544B   | XL/inhibitor                  | 2.5           | Faster cure Mixed pot life ~ 2 weeks  |
|             | Х 6779В    | XL/inhibitor                  | 2.5           | Easy release complex parts Shorter mixed pot life ~ 1-month                           |
|             | X 28992    | Self-bond XL                  | 2.5           | Self-bond silicone to fluorocarbon, fabric / Improved interlayer bond strength        |
| EXTRUSION   | GT 6002A   | Platinum Catalyst             | 1.25          | Excellent higher strength physicals from GP base                                      |
|             | GT 6544B   | XL/inhibitor                  | 2.5           | Faster cure Mixed pot life ~ 2 weeks  |
|             | X 28792    | XL/inhibitor                  | 2.5           | Tight crosslink density, excellent modulus  |
|             | GT 6795B   | XL/inhibitor                  | 2.5           | Easy release complex parts Moderate mixed pot life                                    |
| CALENDARING | GT 5239A   | Platinum Catalyst             | 1             | Achieve higher strength physicals from GP base/ improved comp set                     |
|             | GT 6002A   | Platinum Catalyst             | 1.25          | Easy release, high strength physicals from GP base                                    |
|             | X 5276B    | XL/inhibitor                  | 1             | Easy release from carrier sheets; autoclave and rotocure                              |
| HCR SPONGE  | GT 6002A   | Platinum Catalyst             | 1.25          | -Uniform closed cell sponge   |
|             | GT 5257B   | Sponge XL/inhibitor           | 2.5           |   |
|             | GT 6602A   | Blowing agent                 | 5             | 2X volume expansion   |
| ADHESIVES   | GT 5466    | 1-part sprayable<br>heat-cure | -             | Excellent Bond/ Silicone to plastics, metals, fabric                                  |
|             | X 17593A/B | 2-part 10:1                   | -             | Flowable RTV adhesive<br>Mixed pot life ~ 1 hour<br>Improved interlayer bond strength |
| ADDITIVES   | GT 6206 FR | Flame Retardant               | 2 to 5 pts    | Excellent flame retardancy  |
|             | GT 6606    | Process aid                   | 0.5           | HCR base process aid modifier   |
|             | GT 5603    | High Vinyl Gum                | 1-2 pph       | Vinyl Booster   |